

HD/SD SDI, ASI DISTRIBUTOR TX27 (1 IN TO 6 OUTS)

Distributor TX27 multiplies HD/SD SDI input to 6 outputs (to 3 ASI outputs). Input is equalized and all the outputs – reclocked. Distributor operates at any of 143MB/s, 270MB/s, 1.483/1.485GB/s speed. Standard recognition is automatic. Embedded audio passes-through as well. There are green led indicators on the front panel:

- POWER – power on;
- HD – HD SDI input;
- SD – SD SDI input;
- LOCK – signal presence.

There is 1A fuse inside box. Available as stand alone heavy – duty metal shell unit with external PSU or as 19" 1U rack mount unit with double (single) external PSU.



Technical specifications:

Inputs:

Outputs:

Cable length equalizing:

Standard control:

Connectors:

Power:

Dimensions:

HD/SD SDI, ASI equalized (SMPTE 292M/259M/344M)

6 reclocked HD/SD SDI, (3 ASI) (SMPTE 292M/259M/344M)

SD SDI – up to 340m; SDI – up to 120m

auto

BNC

~220V external PSU with not stabilized +7...+15V output

83x43x35mm



Vilnius g. 215/15, Šiauliai LT-76348, Lithuania

Tel: +37041-525930, +37068786167

www.textus.lt

E-mail: info@textus.lt

Skype: videotekstas