

VIDEOTEKSTA2

HD/SD SDI, ASI DISTRIBUTOR VM27 (1 IN TO 6 OUTS)

Distributor VM27 multiplies HD/SD SDI input to 6 outputs (to 3 ASI outputs). Input is **equalized** and all the outputs – **reclocked**. Distributor operates at any of 143MB/s, 270MB/s, 1.483/1.485GB/s speed. Standard recognition is automatic. Embedded audio passes-through as well. There are green led indicators on the front panel:

- POWER – power on;
- HD – HD SDI input;
- SD – SD SDI input;
- LOCK – signal presence.

There is 1A fuse inside box. Available as stand alone heavy – duty metal shell unit with external PSU or as 19" 1U rack mount unit with double (single) external PSU.



Technical specifications:

Inputs:	HD/SD SDI, ASI equalized (SMPTE 292M/259M/344M)
Outputs:	6 reclocked HD/SD SDI, (3 ASI) (SMPTE 292M/259M/344M)
Cable length equalizing:	SD SDI – up to 340m HD SDI – up to 120m
Standard control:	auto
Connectors:	BNC
Power:	~220V external PSU with not stabilized +7...+15V output
Dimensions:	83x43x35mm

Vilnius g. 215/15, Šiauliai LT-76348, Lithuania

www.textus.lt

E-mail: info@textus.lt

Tel: +37041-525930

Fax: +37041-525930